

**FIXUM PRIMER - EPDM PRIMER**

Revision date: 01-04-2019  
 Print date: 01-04-2019

**SECTION 1: Product and company identification**

1.1 Product identifier  
 Trade name: FIXUM PRIMER - EPDM Primer

1.2 Recommended use of the chemical and restrictions on use  
 Recommended use: Primers  
 Restrictions on use: For professional users only

1.3 Details of the supplier of the safety  
 Zinkunie BV  
 Van Salmstraat 46  
 5281 RS Boxtel  
 The Netherlands  
 T +31(0)411-688339 - F +31(0)411-688343  
 info@zinkunie.nl - www.zinkunie.nl


1.4 Emergency telephone number in case of emergency  
 NATIONAAL VERGIFTIGINGEN INFORMATIE CENTRUM (NVIC): +31302748888

**SECTION 2: Hazards Identification**

2.1 GHS classification of the substance or mixture  
**GHS classification in accordance with 29 CFR 1910.1200 (OSHA HCS 2012) and the Hazardous Products Regulations (WHMIS 2015)**

Flammable liquids: Category 2  
 Skin irritation: Category 2  
 Reproductive toxicity: Category 2  
 Specific target organ toxicity - single exposure: Category 3 (Central nervous system)  
 Specific target organ toxicity - repeated exposure: Category 2  
 Aspiration hazard: Category 1

2.2 GHS label elements

|                            |  |
|----------------------------|--|
| Hazard Pictogram(s)        |   |
| Signal Word(s)             | Danger   |
| Hazard Statement(s)        | H225 - Highly flammable liquid and vapour.<br>H304 - May be fatal if swallowed and enters airways.<br>H315 - Causes skin irritation.<br>H336 - May cause drowsiness or dizziness.<br>H361d - Suspected of damaging the unborn child.<br>H373 - May cause damage to organs through prolonged or repeated exposure.  |
| Precautionary Statement(s) | <b>Prevention:</b><br>P201 - Obtain special instructions before use.<br>P202 - Do not handle until all safety precautions have been read and understood.<br>P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking.<br>P233 - Keep container tightly closed.<br>P240 - Ground/bond container and receiving equipment.<br>P241 - Use explosion-proof electrical/ ventilating/ lighting equipment.<br>P242 - Use only non-sparking tools.<br>P243 - Take precautionary measures against static discharge.<br>P260 - Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.<br>P264 - Wash skin thoroughly after handling.<br>P271 - Use only outdoors or in a well-ventilated area.<br>P280 - Wear protective gloves/ protective clothing/ eye protection/ face protection. |

We aanvaarden geen aansprakelijkheid voor schade, van welke aard ook, welke voortvloeit uit het gebruik van deze gegevens of het desbetreffende product zou ontstaan. Productblad is onder voorbehoud van typ- en drukfouten.

Precautionary Statement(s)

**Response:**

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
 P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.  
 Rinse skin with water/shower.  
 P304 + P340 + P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 Call a POISON CENTER/doctor if you feel unwell.  
 P308 + P313 - IF exposed or concerned: Get medical advice/ attention.  
 P331 - Do NOT induce vomiting.  
 P332 + P313 - If skin irritation occurs: Get medical advice/ attention.  
 P362 - Take off contaminated clothing and wash before reuse.  
 P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.  
 P403 + P235 - Store in a well-ventilated place. Keep cool.  
 P405 - Store locked up.

**Disposal:**

P501 - Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

2.3 Other hazards  
 None known.

**SECTION 3: Composition/information on ingredients**

3.1 Hazardous components

| Chemical name                           | CAS No.    | Concentration (%) |
|---|------------|-------------------|
| Toluene                                 | 108-88-3   | >= 30 - <= 60     |
| Naphtha (petroleum), hydrotreated light | 64742-49-0 | >= 30 - <= 60     |

**SECTION 4: First Aid Measures**

|  |  |
|--|--|
| General advice:  | Do not leave the victim unattended.  |
| If inhaled:  | Remove to fresh air immediately. Get medical attention immediately.<br>If breathing is irregular or stopped, administer artificial respiration.  |
| In case of skin contact:                                     | In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately.   |
| In case of eye contact:                                      | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.<br>If easy to do, remove contact lens, if worn. Protect unharmed eye.<br>If eye irritation persists, consult a specialist.  |
| If swallowed:  | DO NOT induce vomiting unless directed to do so by a physician or poison control center.<br>Gently wipe or rinse the inside of the mouth with water.<br>Never give anything by mouth to an unconscious person.<br>Get medical attention immediately.<br>If breathing is irregular or stopped, administer artificial respiration. |
| Most important symptoms and effects, both acute and delayed: | May be fatal if swallowed and enters airways.<br>Causes skin irritation.<br>May cause drowsiness or dizziness.<br>Suspected of damaging the unborn child.<br>May cause damage to organs through prolonged or repeated exposure.  |

## SECTION 5: Firefighting Measures

### 5.1 Extinguishing media

|  |  |
|--|--|
| Suitable extinguishing media:                  | Carbon dioxide (CO <sub>2</sub> ).<br>Foam.<br>Dry chemical.<br>Water spray. |
| Unsuitable extinguishing media:                | High volume water jet.   |
| Hazardous combustion products:                 | Carbon oxides.   |
| Further information:                           | Standard procedure for chemical fires.                                       |
| Special protective equipment for firefighters: | Wear self-contained breathing apparatus for firefighting if necessary.       |

## SECTION 6: Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Use personal protective equipment.

### 6.2 Methods and material for containment and cleaning up

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

## SECTION 7: Handling and Storage

|  |   |
|--|---|
| Advice on protection against fire and explosion: | Normal measures for preventive fire protection.   |
| Advice on safe handling:                         | For personal protection see section 8.<br>Smoking, eating and drinking should be prohibited in the application area.  |
| Conditions for safe storage:                     | Electrical installations / working materials must comply with the technological safety standards.<br>Keep containers tightly closed in a dry, cool and well-ventilated place. |
| Materials to avoid:                              | Keep away from oxidizing agents and strongly acid or alkaline materials.  |
| Further information on storage stability:        | Stable at normal ambient temperature and pressure.  |

## SECTION 8: Exposure Controls/Personal Protection

### Components with workplace control parameters

| Components                              | CAS-No.    | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis     |
|---|------------|-------------------------------|--|-----------|
| Toluene                                 | 108-88-3   | TWA                           | 20 ppm   | ACGIH     |
|   |            | TWA                           | 100 ppm<br>375 mg/m <sup>3</sup>               | NIOSH REL |
|   |            | ST                            | 150 ppm<br>560 mg/m <sup>3</sup>               | NIOSH REL |
|   |            | TWA                           | 200 ppm  | OSHA      |
|   |            | CEIL                          | 300 ppm  | OSHA      |
|   |            | Peak                          | 500 ppm (10 minutes)                           | OSHA      |
| Naphtha (petroleum), hydrotreated light | 64742-49-0 | TWA                           | 500 ppm<br>2,000 mg/m <sup>3</sup>             | OSHA      |

**Biological occupational exposure limits**

| Components | CAS-No.  | Control parameters | Biological specimen | Sampling time  | Permissible concentration | Basis        |
|------------|----------|--------------------|---------------------|--|---------------------------|--------------|
| toluene    | 108-88-3 | Toluene            | In blood            | Prior to last shift of workweek                          | 0.02 mg/l                 | ACGIH<br>BEI |
|            |          | Toluene            | Urine               | End of shift (As soon as possible after exposure ceases) | 0.03 mg/l                 | ACGIH<br>BEI |
|            |          | o-Cresol           | Urine               | End of shift (As soon as possible after exposure ceases) | 0.3 mg/g Creatinine       | ACGIH<br>BEI |

**Personal protective equipment**

|                           |   |
|---------------------------|---|
| Respiratory protection:   | General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection. |
| Hand protection material: | Nitrile rubber  |
| Remarks:                  | Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.  |
| Eye protection:           | Wear safety glasses with side shields or goggles.   |
| Skin and body protection: | Wear protective clothing, such as long-sleeved shirts and pants. Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.   |
| Hygiene measures:         | Handle in accordance with good industrial hygiene and safety practice. Written instructions for handling must be available at the work place.   |

**SECTION 9: Physical and Chemical Properties**

|  |                                 |
|--|---------------------------------|
| Appearance:                              | Liquid                          |
| Colour:                                  | Blue                            |
| Odour:                                   | Characteristic                  |
| Odour Threshold:                         | No data available               |
| pH:                                      | No data available               |
| Melting point/freezing point:            | No data available               |
| Initial boiling point and boiling range: | 98 °C                           |
| Flash point:                             | -4 °C                           |
| Evaporation rate:                        | No data available               |
| Flammability (solid, gas):               | Not applicable                  |
| Upper explosion limit:                   | 7.0 %(V)                        |
| Lower explosion limit:                   | 1.1 %(V)                        |
| Vapour pressure:                         | 29 hPa (20 °C)                  |
| Relative vapour density:                 | No data available               |
| Relative density:                        | No data available               |
| Density:                                 | 0.808 g/cm <sup>3</sup> (20 °C) |
| Solubility(ies)                          |                                 |
| Water solubility:                        | Immiscible                      |
| Solubility in other solvents:            | No data available               |
| Partition coefficient: n-octanol/water:  | No data available               |
| Auto-ignition temperature:               | 215 °C                          |
| Thermal decomposition:                   | No data available               |
| Viscosity                                |                                 |
| Viscosity, dynamic:                      | No data available               |
| Viscosity, kinematic:                    | <= 20.5 mm <sup>2</sup> /s      |

## SECTION 10: Stability and Reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical Stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

None known. No hazards to be specially mentioned.

### 10.4 Conditions to avoid

Heat, flames and sparks.

### 10.5 Incompatible materials

Strong oxidizing agents

## SECTION 11: Toxicological Information

### Acute toxicity

Not classified based on available information.

#### Product:

Acute inhalation toxicity: Acute toxicity estimate : 66.12 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity: Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

### Acute toxicity

#### Components:

##### Toluene:

Acute oral toxicity: LD50 Oral (Rat, male): 5,580 mg/kg

Acute inhalation toxicity: LC50 (Rat): 28.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity: LD50 (Rabbit): > 12,267 mg/kg

### Acute toxicity

#### Naphtha (petroleum), hydrotreated light:

Acute oral toxicity: LD50 (Rat, male and female): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity: LC50 (Rat): > 5.61 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
GLP: yes  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity: LD50 (Rabbit, male and female): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

### Skin corrosion/irritation

#### Components:

##### Toluene:

Species: Rabbit  
Result: Irritating to skin.

Respiratory sensitisation: Not classified based on available information.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Components:

Toluene:

Reproductive toxicity - Assessment: Suspected of damaging the unborn child., Some evidence of adverse effects on development, based on animal experiments.

**STOT - single exposure**

Components:

Toluene:

Assessment: May cause drowsiness or dizziness.

**STOT - repeated exposure**

Components:

Toluene:

Assessment: May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity**

May be fatal if swallowed and enters airways.

Components:

Toluene:

May be fatal if swallowed and enters airways.

Naphtha (petroleum), hydrotreated light:

May be fatal if swallowed and enters airways.

**Experience with human exposure**

Components:

toluene:

Skin contact: Remarks: Prolonged skin contact may defat the skin and produce dermatitis.

**Further information**

Product:

Remarks: No data available

## SECTION 12: Ecological Information

**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

Components:

Toluene:

Partition coefficient: n-octanol/water: Pow: 2.7

Naphtha (petroleum), hydrotreated light:

Partition coefficient: n-octanol/water: log Pow: ca. 3.3 - 6

**Mobility in soil**

No data available

**Other adverse effects**

Product:

Ozone-Depletion Potential:

Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information:

No data available

## SECTION 13: Disposal Considerations

**Disposal methods**

Disposal of residual product:

Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Contaminated packaging:

Empty containers should be taken to an approved waste handling site for recycling or disposal. Packaging that cannot be reused after cleaning must be disposed or recycled in accordance with all federal, national and local regulations.

## SECTION 14: Transport Information

### International transport regulations

U.S. Department of Transportation: UN 1133, Adhesives, 3, II.

LIMITED QUANTITY if shipped in inner packagings not over 5.0 L (1.3 gallons) net capacity each, packed in a strong outer packaging.

## SECTION 15: Regulatory Information

### TSCA list

TSCA - 5(a) Significant

New Use Rule List of Chemicals: No substances are subject to a Significant New Use Rule.

U.S. Toxic Substances Control

Act (TSCA) Section 12(b) Export

Notification (40 CFR 707, Subpt D): No substances are subject to TSCA 12(b) export notification requirements.

### EPCRA - Emergency Planning and Community Right-to-Know Act

SARA 311/312 Hazards: Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard

SARA 302: This material does not contain any components with a section 302 EHS TPQ.

SARA 313: The following components are subject to reporting levels established by SARA Title III, Section 313:  
toluene 108-88-3 30 - 60 %

### Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):  
toluene 108-88-3 30 - 60 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):  
toluene 108-88-3 30 - 60 %

### US. Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)

toluene 108-88-3  
benzene 71-43-2  
formaldehyde 50-00-0

### US. Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

toluene 108-88-3  
naphtha (petroleum), hydrotreated light 64742-49-0

### US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

**WARNING:** This product can expose you to chemicals including ethylbenzene, benzene, naphthalene, cumene, formaldehyde, which is/are known to the State of California to cause cancer, and toluene, benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### California List of Hazardous Substances

toluene 108-88-3

### California Permissible Exposure Limits for Chemical Contaminants

toluene 108-88-3

### The components of this product are reported in the following inventories:

TSCA: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

DSL: All components of this product are on the Canadian DSL

## SECTION 16: Other Information

### Further information

Revision Date: 01-04-2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.