

Safety data sheet
according to 1907/2006/EC, Article 31 and Regulation
2020/878

Printing date 07.02.2024

Version number 2 (replaces version 1)

Revision: 07.02.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: PRIMER S**
- **Article number:** 101_0020
- **UFI:** YRA1-W0V4-300C-49HD
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Life cycle stages**
C Consumer use
PW Widespread use by professional workers
- **Sector of Use**
SU21 Consumer uses: Private households / general public / consumers
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Process category**
PROC10 Roller application or brushing
PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
- **Environmental release category**
ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
- **Application of the substance / the mixture** Etch primer, Wash primer
- **Uses advised against** Non-ventilated environments
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
COPERNIT SPA
VIA PROVINCIALE EST, 64
46020 PEGOGNAGA (MN) Italia
tel. +39 0376 554911
fax +39 0376 550177
- **Further information obtainable from:** info@copernit.it
- **1.4 Emergency telephone number:**
National Poisons Information Service (NPIS) - Email:
director.birmingham.unit@npis.org
Members of the public seeking specific information on poisons should contact:
England and Wales: NHS 111 - dial 111;
Scotland: NHS 24 - dial 111;
N Ireland: Contact your local GP or pharmacist during normal hours; click here
(www.gpoutofhours.hscni.net/) for GP services Out-of-Hours;
Republic of Ireland: 01 809 2166

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31 and Regulation
2020/878

Printing date 07.02.2024

Version number 2 (replaces version 1)

Revision: 07.02.2024

Trade name: PRIMER S

(Contd. of page 1)

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

toluene
Solvent naphtha (petroleum), light arom.
styrene
xylene

· **Hazard statements**

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H361d Suspected of damaging the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to the hearing organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves / eye protection / face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31 and Regulation
2020/878

Printing date 07.02.2024

Version number 2 (replaces version 1)

Revision: 07.02.2024

Trade name: PRIMER S

(Contd. of page 2)

· **Determination of endocrine-disrupting properties**

78-93-3 butanone

List II

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-00-3	toluene ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	25-30%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-XXXX	Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336, EUH066	5-10%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-XXXX	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-XXXX	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336, EUH066	2.5-5%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46-XXXX	ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	2.5-5%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-XXXX	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≤2.5%
CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0	styrene ⚠ Flam. Liq. 3, H226; ⚠ Repr. 2, H361d; STOT RE 1, H372; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	≤2.5%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	≤2.5%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43-XXXX	butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≤2.5%
CAS: 110-54-3 EINECS: 203-777-6 Index number: 601-037-00-0	n-hexane ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 Specific concentration limit: STOT RE 2; H373: C ≥ 5 %	≥0.25-<2.5%

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31 and Regulation
2020/878

Printing date 07.02.2024

Version number 2 (replaces version 1)

Revision: 07.02.2024

Trade name: PRIMER S

CAS: 142-82-5 EINECS: 205-563-8 Index number: 601-008-00-2 Reg.nr.: 01-2119475515-33-XXXX	heptane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	(Contd. of page 3) ≥0.25-<2.5%
--	---	-----------------------------------

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing equipment only after contaminated clothing have been completely removed.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

· **5.3 Advice for firefighters**

· **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31 and Regulation
2020/878

Printing date 07.02.2024

Version number 2 (replaces version 1)

Revision: 07.02.2024

Trade name: PRIMER S

See Section 13 for disposal information.

(Contd. of page 4)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Protect against electrostatic charges.
Keep respiratory protective device available.
Keep ignition sources away - Do not smoke.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Provide solvent resistant, sealed floor.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

108-88-3 toluene

IOELV	Short-term value: 384 mg/m ³ , 100 ppm Long-term value: 192 mg/m ³ , 50 ppm Skin
-------	--

1330-20-7 xylene

IOELV	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin
-------	--

123-86-4 n-butyl acetate

IOELV	Short-term value: 723 mg/m ³ , 150 ppm Long-term value: 241 mg/m ³ , 50 ppm
-------	--

141-78-6 ethyl acetate

IOELV	Short-term value: 1468 mg/m ³ , 400 ppm Long-term value: 734 mg/m ³ , 200 ppm
-------	--

67-64-1 acetone

IOELV	Long-term value: 1210 mg/m ³ , 500 ppm
-------	---

100-41-4 ethylbenzene

IOELV	Short-term value: 884 mg/m ³ , 200 ppm Long-term value: 442 mg/m ³ , 100 ppm Skin
-------	---

78-93-3 butanone

IOELV	Short-term value: 900 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm
-------	---

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31 and Regulation
2020/878

Printing date 07.02.2024

Version number 2 (replaces version 1)

Revision: 07.02.2024

Trade name: PRIMER S

(Contd. of page 5)

110-54-3 n-hexane		
IOELV	Long-term value: 72 mg/m ³ , 20 ppm	
142-82-5 heptane		
IOELV	Long-term value: 2085 mg/m ³ , 500 ppm	
· DNELs		
108-88-3 toluene		
Oral	DNEL	8.13 mg/kg/day (worker)
Dermal	DNEL	384 mg/kg/day (worker)
Inhalative	DNEL	192 mg/m ³ (worker)
Solvent naphtha (petroleum), light arom.		
Oral	DNEL	25 mg/kg/day (worker)
Inhalative	DNEL	150 mg/m ³ (worker)
1330-20-7 xylene		
Oral	DNEL	12.5 mg/kg/day (worker)
Dermal	DNEL	212 mg/kg/day (worker)
Inhalative	DNEL	221 mg/m ³ (worker)
141-78-6 ethyl acetate		
Inhalative	DNEL	734 mg/m ³ (worker)
67-64-1 acetone		
Dermal	DNEL	186 mg/kg/day (worker)
Inhalative	DNEL	1,210 mg/m ³ (worker)
78-93-3 butanone		
Dermal	DNEL	1,161 mg/kg/day (worker)
142-82-5 heptane		
Dermal	DNEL	300 mg/kg/day (worker)
Inhalative	DNEL	2,085 mg/m ³ (worker)
· PNECs		
1330-20-7 xylene		
PNEC	0.32 mg/l	
141-78-6 ethyl acetate		
PNEC	0.24 mg/l	

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Respiratory protection:**

- Use suitable respiratory protective device in case of insufficient ventilation.
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31 and Regulation
2020/878

Printing date 07.02.2024

Version number 2 (replaces version 1)

Revision: 07.02.2024

Trade name: PRIMER S

(Contd. of page 6)

· **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Butyl rubber, BR

Nitrile rubber, NBR

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Tightly sealed goggles

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

· **Colour:**

Black

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

110-111 °C (108-88-3 toluene)

· **Flammability**

Highly flammable.

· **Lower and upper explosion limit**

· **Lower:**

1.2 Vol % (108-88-3 toluene)

· **Upper:**

7 Vol % (108-88-3 toluene)

· **Flash point:**

12 °C

· **Auto-ignition temperature:**

>450 °C (64742-95-6 Solvent naphtha (petroleum), light arom.)

· **Decomposition temperature:**

Not determined.

· **pH**

Mixture is non-soluble (in water).

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **Dynamic:**

Not determined.

· **Solubility**

· **water:**

Not miscible or difficult to mix.

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Vapour pressure at 20 °C:**

29 hPa (108-88-3 toluene)

· **Vapour pressure at 50 °C:**

124 hPa

· **Density and/or relative density**

· **Density at 20 °C:**

0.9-0.96 g/cm³

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31 and Regulation
2020/878

Printing date 07.02.2024

Version number 2 (replaces version 1)

Revision: 07.02.2024

Trade name: PRIMER S

(Contd. of page 7)

- **9.2 Other information**
- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Solvent separation test:**
- **VOC (EC)** 520-600 g/l
58.82 %
- **Change in condition**
- **Evaporation rate** Not determined.

- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Highly flammable liquid and vapour.
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** No further relevant information available.
- **10.3 Possibility of hazardous reactions** Reacts with strong oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Dermal	LD50	27,473 mg/kg (rabbit)
--------	------	-----------------------

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31 and Regulation
2020/878

Printing date 07.02.2024

Version number 2 (replaces version 1)

Revision: 07.02.2024

Trade name: PRIMER S

(Contd. of page 8)

108-88-3 toluene		
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
123-86-4 n-butyl acetate		
Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)
141-78-6 ethyl acetate		
Oral	LD50	4,934 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
100-42-5 styrene		
Oral	LD50	5,000 mg/kg (rat)
Inhalative	LC50/4 h	24 mg/l (rat)
100-41-4 ethylbenzene		
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)
78-93-3 butanone		
Oral	LD50	2,737 mg/kg (rat)
Dermal	LD50	6,480 mg/kg (rabbit)
Inhalative	LC50/4 h	23.5 mg/l (rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Suspected of damaging the unborn child.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure**
May cause damage to the hearing organs through prolonged or repeated exposure.
- **Aspiration hazard** May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

78-93-3 | butanone

List II

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31 and Regulation
2020/878

Printing date 07.02.2024

Version number 2 (replaces version 1)

Revision: 07.02.2024

Trade name: PRIMER S

(Contd. of page 9)

· **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects**

- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Harmful to aquatic organisms

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

The classification in the European waste catalogue must be done for the branch and the process type.

· **Uncleaned packaging:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA** UN1263

· **14.2 UN proper shipping name**

· **ADR, IMDG, IATA** PAINT

· **14.3 Transport hazard class(es)**

· **ADR, IMDG, IATA**



· **Class** 3 Flammable liquids.
· **Label** 3

· **14.4 Packing group**

· **ADR, IMDG, IATA** II

· **14.5 Environmental hazards:** Not applicable.

· **14.6 Special precautions for user** Warning: Flammable liquids.

· **Hazard identification number (Kemler code):** 33

· **EMS Number:** F-E,S-E

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31 and Regulation
2020/878

Printing date 07.02.2024

Version number 2 (replaces version 1)

Revision: 07.02.2024

Trade name: PRIMER S

(Contd. of page 10)

· Stowage Category	B
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2004/42/EC**
Product type: PAINTS AND VARNISHES
 - Product subcategory: Binding primers
 - Solvent-borne coatings, Limit value: 750 g/l
- VOC: 520-600 g/l
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 48

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

108-88-3	toluene	3
67-64-1	acetone	3
78-93-3	butanone	3

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31 and Regulation
2020/878

Printing date 07.02.2024

Version number 2 (replaces version 1)

Revision: 07.02.2024

Trade name: PRIMER S

(Contd. of page 11)

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

108-88-3	toluene	3
67-64-1	acetone	3
78-93-3	butanone	3

· **National regulations:**

· **Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H361f Suspected of damaging fertility.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· **Classification according to Regulation (EC) No 1272/2008**

Flammable liquids	Bridging principles
Skin corrosion/irritation Serious eye damage/irritation Reproductive toxicity Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
Aspiration hazard	Expert judgement

· **Date of previous version:** 13.12.2022

· **Version number of previous version:** 1

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31 and Regulation
2020/878

Printing date 07.02.2024

Version number 2 (replaces version 1)

Revision: 07.02.2024

Trade name: PRIMER S

(Contd. of page 12)

EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Repr. 2: Reproductive toxicity – Category 2
 Repr. 2: Reproductive toxicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
 * **Data compared to the previous version altered.**

Annex: Exposure scenario

- **Short title of the exposure scenario**
- **Sector of Use**
 SU21 Consumer uses: Private households / general public / consumers
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Process category**
 PROC10 Roller application or brushing
 PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
- **Environmental release category**
 ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
- **Description of the activities / processes covered in the Exposure Scenario**
 See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
- **Duration and frequency** 5 workdays/week.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** The substance is main component.
- **Used amount per time or activity** According to directions for use.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting worker exposure**
 Avoid contact with the skin.
 Take precautionary measures against static discharge.
 Keep away from sources of ignition - No smoking.
 Outdoor application.
 Avoid contact with eyes.
- **Other operational conditions affecting consumer exposure** No special measures required.
- **Other operational conditions affecting consumer exposure during the use of the product**
 Not applicable.

(Contd. on page 14)

Safety data sheet
according to 1907/2006/EC, Article 31 and Regulation
2020/878

Printing date 07.02.2024

Version number 2 (replaces version 1)

Revision: 07.02.2024

Trade name: PRIMER S

(Contd. of page 13)

- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures**
Provide explosion-proof electrical equipment.
Ensure that suitable extractors are available on processing machines
- **Personal protective measures**
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Pregnant women should strictly avoid inhalation or skin contact.
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
Avoid contact with the eyes.
Tightly sealed goggles
- **Measures for consumer protection** Ensure adequate labelling.
- **Environmental protection measures**
- **Water** No special measures required.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** Not relevant for this Exposure Scenario.
- **Guidance for downstream users** No further relevant information available.